



Feature

- Third-party IP cameras supported with ONVIF conformance
- Integrated 5 100M PoE +(802.3at) interfaces
- Up to 300 meters long distance transmission of the PoE
- Support PnP for easy IPC discovery and usage
- Up to 5 Megapixels resolution recording storage and playback
- Simultaneous HDMI and VGA output the resolution is up to 1080P
- Up to 8 channels synchronously playback
- Support instant playback
- Support corridor mode

MODEL No.	QH-N4108F-H
VIDEO/AUDIO INPUT	
IP Video Input	8 CH
Two-way Audio Input	1 CH, RCA (2.0 Vp-p, 1kΩ)
NETWORK	
Incoming Bandwidth	64Mbps
VIDEO/AUDIO OUTPUT	
HDMI Output	1
VGA Output	1
Audio Output	1 CH, RCA
DECODING	
Live View / Playback Resolution	4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Recording Resolution	4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Synchronous Playback	8 CH

HARD DISK DRIVE (HDD)	
SATA	2
Capacity	Up to 4TB for each disk
EXTERNAL INTERFACE	
Network Interface	1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
Serial Interface	NA
USB Interface	1 USB 2.0 + 1 USB 3.0
Alarm In	NA
Alarm Out	NA
PoE	
Interface	8 independent 10 /100 Mbps PoE Ethernet interfaces
Supported Standard	802.3at
GENERAL	
Power Supply	52V, DC
Consumption	94W (Fully Configured)
Working Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Working Humidity	10% – 90%
Dimensions	43.6mm × 360.0mm × 254.3mm (1.72" × 14.17" × 10.01"), 1U
Weight (without HDD)	1.5KG